Summit ACCEL





Product Specifications

Construction Nominal Size Overall Thickness Wear Layer Edge Detail Coverage Installation Warranty Flame Spread ASTM E 648 Smoke Evolution ASTM E 662 Acoustical Performance Temperature Performance Unique Visuals Luxury Vinyl Plank (LVP) 6.5" x 48" 2.0 mm 12 mil, Resolute Diamond Shield Square 18 pcs. per ctn; 38.88 sq. ft. per ctn Glue Down, No Acclimation Required 35-Year Limited Residential / 5-Year Limited Commercial 0.45 W/cm² or more Class I 450 or less IIC 41, STC 52, Delta IIC 13 32°F - 160°F 30 per design



Lose the wait - Summit ACCEL is ready to be installed right away without any wasted acclimation time.

Unrivaled Performance

Resolute Diamond Shield resists stains, even driveway sealer to keep floors looking newer, longer. The Rebound Core provides superior indentresistance.

Made in the USA

Ready to ship right away with no delays. Summit ACCEL floors are manufactured in the USA with global and domestic content.

100% Waterproof Planks

Summit ACCEL flooring is perfect for high moisture areas such as kitchens, bathrooms and laundry rooms

Outperforms Thermal Pest Control

Avoid damage from bed bug heat treatment. Summit ACCEL comfortably withstands temperatures up to 160°F, outmatching the lethal temperature for bed bugs (118°F - 130°F).

Resolute Diamond Shield Coating	
Wear Layer	
Design Layer	
Rebound Core	
Fiberglass Layer	
Base	



Belmont



Hialeah



Churchill Downs



Santa Anita



Pimlico





Saratoga

CUSTOMER SERVICE 800-874-1930 • WWW.CAINBULTMAN.COM